

**AFFORDABLE
ANALOG / DIGITAL
REFRACTOMETERS**

*for
SAP and SYRUP*



Model # RHB-32 0-32 brix

Model # RHB-82 45-82 brix



**AUTO CONTROLS
and
ACCESSORIES**



call for your CD catalog



CANADA: ROJAN (Ron Beaudreau)
tel: 1(519)578-0238
e-mail: rrojan2002@yahoo.com



220 River Rd., Schroon Lake, NY 12870
tel: 1(518)532-7922 fax: 1(518)532-7386
www.marcland-usa.com
BOB CROOKS

**REFRACTOMETERS
DIGITAL and ANALOG**



PA-202X
Sap / Syrup



PAL-MAPLE
Sap / Syrup



HI-96801
Sap / Syrup



RHB-32
Sap
RHB-82
Syrup





HI-96801

SAP / SYRUP

RANGE: 0.0 to 85.0% Brix
RESOLUTION: 0.1% Brix
ACCURACY: 0.2% Brix
AMBIENT TEMPERATURE:
 50 to 104 deg F
MEASUREMENT TEMPERATURE:
 50 to 104 deg F
POWER: 1 x 9v Batteries
MEASUREMENT TIME:
 2 seconds
APPLICATIONS:
 (wide range sugar content)
CLEAN and ZERO with water



MARCLAND



PAL-MAPLE

SAP / SYRUP

RANGE: 0.0 to 85.0% Brix
RESOLUTION: 0.1% Brix
ACCURACY: 0.2% Brix
AMBIENT TEMPERATURE:
 50 to 104 deg F
MEASUREMENT TEMPERATURE:
 50 to 167 deg F
POWER: 2 x AAA Batteries
MEASUREMENT TIME:
 3 seconds
APPLICATIONS:
 (wide range sugar content)
CLEAN and ZERO with water



MARCLAND



PA-202X

SAP / SYRUP

RANGE: 0.0 to 85.0% Brix
RESOLUTION: 0.1% Brix
ACCURACY: 0.1% Brix
AMBIENT TEMPERATURE:
 32 to 104 deg F
MEASUREMENT TEMPERATURE:
 32 to 167 deg F
POWER: 2 x AAA Batteries
MEASUREMENT TIME:
 5 seconds
APPLICATIONS:
 (wide range sugar content)
CLEAN and ZERO with water



MARCLAND